

For reducing the exhaust noise generated by pneumatic equipment  
 Operating pressure: Max. 12 bar  
 Operating temperature: -10°C to +150 °C  
 Port: Rp thread acc. to EN ISO 228-1  
 More information: Please contact [cen-ping@163.com](mailto:cen-ping@163.com)




Silencers, sintered bronze, slotted

Art No.	Thread	a/f	A	B	C
564-1	G 1/8	-	6.5	12.5	9.5
564-2	G 1/4	-	6.5	13.5	13.0
564-3	G 3/8	-	7.5	16.0	16.0
564-4	G 1/2	-	10.0	19.6	20.5



Silencers, sintered bronze, flat type with female thread

Art No.	Thread	a/f	A	B	C
565-0	M5	8	-	8.5	5.0
565-1	G 1/8	13	-	10.5	9.0
565-2	G 1/4	16	-	11.5	11.0
565-3	G 3/8	19	-	12.5	15.0
565-4	G 1/2	24	-	13.5	20.0



For reducing the exhaust noise generated by pneumatic equipment  
 Operating pressure: 0 to 8 bar  
 Operating temperature: -10°C to +250°C  
 Noise level at 6 bar: 71~108 dB(A)  
 More information: Please contact [cen-ping@163.com](mailto:cen-ping@163.com)



Silencers, sintered bronze, with hexagon nut

Art No.	Thread	a/f	A	B	C
567-1	G 1/8	13	6.0	28.0	8.0
567-2	G 1/4	17	8.0	34.0	12.0
567-3	G 3/8	22	10.0	36.0	15.0
567-4	G 1/2	27	12.0	44.0	19.0
567-5	G 3/4	32	14.0	54.0	22.0
567-6	G 1	41	16.0	66.0	28.0



Silencers, sintered bronze, with brass hexagon nut and brass thread

Art No.	Thread	a/f	A	B	C
567-0/M	M5	9	5.0	18.5	4.0
567-1/M	G 1/8	12	4.5	21.0	8.5
567-2/M	G 1/4	15	6.0	28.0	11.0
567-3/M	G 3/8	19	7.0	35.5	14.0
567-4/M	G 1/2	23	8.0	41.5	16.0
567-5/M	G 3/4	30	9.0	53.0	21.0
567-6/M	G 1	36	12.0	67.0	27.0



Silencers, sintered bronze, slotted

Art No.	Thread	a/f	A	B	C
568-1	G 1/8	-	5.5	21.0	8.0
568-2	G 1/4	-	8.5	27.0	10.0
568-3	G 3/8	-	11.0	36.0	15.0
568-4	G 1/2	-	11.0	44.0	19.0
568-5	G 3/4	-	12.0	65.0	20.0
568-6	G 1	-	15.0	75.0	26.5



Silencers, sintered bronze, flat type with male thread

Art No.	Thread	a/f	A	B	C
569-0	M5	8	4.0	8.0	7.8
569-1	G 1/8	13	6.0	13.0	12.8
569-2	G 1/4	15	7.5	16.5	14.8
569-3	G 3/8	19	7.5	16.5	18.8
569-4	G 1/2	24	9.0	18.5	23.0



Exhaust mufflers, sintered bronze

Art No.	Thread	SW	A	B	C
566-1	G 1/8	14	7.0	23	28
566-2	G 1/4	17	11.0	32	38
566-3	G 3/8	19	12.5	32	38
566-4	G 1/2	22	16.0	39	48
566-5	G 3/4	27	17.0	45	53
566-6	G 1	34	18.0	50	62

For more information about exhaust mufflers, please contact [cen-ping@163.com](mailto:cen-ping@163.com)

